INTELLOFA	CLASSIFICATION		7R008100080003-5 ^{25X1}	W
	CENTRAL INTELLIGE	NCE AGENCY	REPORT NO.	11/4
	INFORMATION	REPORT	CD NO.	25
COUNTRY	Germany (Russian Zone)	25X1	DATE DISTR. 17 July 1	051
SUBJECT			NO. OF PAGES 1	L 7 J.A.
	Railroad Line		· · · · · ·	
			NO. OF ENCLS.	25
			SUPPLEMENT TO REPORT NO.	
SS OF THE UNIT	HT CONVAIRS INFORMATION AFFECTING THE MITTORAL DEFENSE OF STATES WITHIN THE SEAMING OF THE ESPICIACH ACT SO BY SALES ALEMENTS, HT STRAIGHISTICS OF THE EXPELIATION WITH A SEA OF THE SEAMENT OF THE SEAME	THIS IS UNEX	ALUATED INFORMATION	2
		X(* **	
	(N 53/Z 69) railroad line was take	m over rrom brr	vara combantas tu tata	
2	capacity was to be increased so as This required the installation of of bridges and culverts. The train by the installation of six crossin Neustadt/Dosse was also provided f southern curve at the Loewenberg r The cost of the project was estima were to be spent in early 1951. In	to be capable of heavier S 49 type density on the g points. Constr for. The line was cailroad station.	ons axle pressure. The line of 20 tons axle pressure. The line of 20 tons axle pressure. The line of a rails and reinforcement line was to be increased ruction of a rail link near aplanned to terminate in a composite of the state of the st	
2	capacity was to be increased so as This required the installation of of bridges and culverts. The train by the installation of six crossin Neustadt/Dosse was also provided f southern curve at the Loewenberg r . The cost of the project was estima	to be capable of heavier S 49 type density on the groints. Construction. The line was ailroad station. Ited at 10,000,00 mid-April. 1951, the former Rather the original graink southeast of ilroad line, is rossing points were willow, and Cramber of the week of the original graink southeast of the	ons axle pressure. The line of 20 tons axle pressure. The line of 20 tons axle pressure. The line of 20 tons axle pressure. The results and reinforcement line was to be increased ruction of a rail link near splanned to terminate in a complete of which 3,400, the reinforced line was the revelocement of the replaced by \$49, 8a, and ravel ballast was replaced to Neustadt/Dosse, which completed. The railroad were built near Spaatz, rieben. The line was conned	000
3	capacity was to be increased so as This required the installation of of bridges and culverts. The train by the installation of six crossin Neustadt/Dosse was also provided f southern curve at the Loewenberg r. The cost of the project was estimated to be spent in early 1951. In opened. Telmforcement of the road bed of two was completed. The 6d type rails of 15c type rails. Seventy percent of by broken stone. The 1.5-km rail is passes under the Berlin-Hamburg rated underpass is nearing completion. C. Friedrichsdorf, Barsikow, Wildberg in mid-April 1951. Declassified Class. Changed To: Ts & C. Mith.: HR 70-2 Late:25_HH1978_By:	to be capable of heavier S 49 type density on the groints. Construction. The line was ailroad station. Ited at 10,000,00 mid-April. 1951, the former Rather on this line were the original graink southeast or ilroad line, is rossing points were with the construction of the construction o	one axle pressure. The line of 20 tons axle pressure. The line of 20 tons axle pressure. The line was to be increased ruction of a rail link near a planned to terminate in a completed. The railroad recompleted. The railroad recompleted. The railroad recompleted. The railroad recompleted.	000
3	capacity was to be increased so as This required the installation of of bridges and culverts. The train by the installation of six crossin Neustadt/Dosse was also provided f southern curve at the Loewenberg r. The cost of the project was estimated to be spent in early 1951. In opened. Telmforcement of the road bed of two was completed. The 6d type rails of 15c type rails. Seventy percent of by broken stone. The 1.5-km rail is passes under the Berlin-Hamburg rated underpass is nearing completion. C. Friedrichsdorf, Barsikow, Wildberg in mid-April 1951. Declassified Class. Changed To: Ts & C. Mith.: HR 70-2 Late:25_HH1978_By:	to be capable of heavier S 49 type density on the groints. Construction. The line was ailroad station. Ited at 10,000,00 mid-April. 1951, the former Rather the original graink southeast of ilroad line, is rossing points were willow, and Cramber of the week of the original graink southeast of the	ons axle pressure. The line of 20 tons axle pressure. The line of 20 tons axle pressure. The line of 20 tons axle pressure. The results and reinforcement line was to be increased ruction of a rail link near splanned to terminate in a complete of which 3,400, the reinforced line was the revelocement of the replaced by \$49, 8a, and ravel ballast was replaced to Neustadt/Dosse, which completed. The railroad were built near Spaatz, rieben. The line was conned	000